
Beoview 7 Porter concierge unit



Reference: BEOVIEW 7 PORTER





Main characteristics



- IP digital installation.
- · Front of tempered glass in black finish.
- Handset, casing and table stand entirely made of black anodized
- 7" colour TFT LCD with capacitive touch screen.
- · Includes table stand.

Dimensions: 265(W) x 185(H) x 158(D) mm.

Additional information

- Serverless system: don't requires a computer connected on the network.
- Supports Class A, Class B and Class C Ethernet networks.
- Easily upgradeable firmware, being possible to add new or under request features over already installed systems.
- · Intuitive graphic user interface.
- On screen labelling, showing information of the calling panel or apartment.
- · Real time video streaming.
- Privacy on audio, video and door open progresses.
- · Call volume regulation.
- Video spy and auto switch-on functions of all panels being able to call the concierge unit.
- Picture memory of missed calls, with time and date stamp. Missed calls from the apartments are also stored.
- Two calling methods: direct entry of the apartment code through the virtual keypad or by searching the tenant name in the repertory.
- Is it possible to connect units in daisy chain configuration by usingT-SWITCH.
- Concierge units are to be connected to a PoE switch output or to a PoE injector. Maximum consumption is 6W.

Accessories

• PCAM/LCC IP concierge camera

• PSU-8023AF one port PoE injector

Visit in the website: https://www.golmar.es/products/beoview-7-porter-concierge-unit